Docket #: S06-255

# Reduction of Thermal Drift in a Fiber Optic Gyroscope

An optical sensor includes an optical coupler. The optical sensor further includes a photonic bandgap fiber having a hollow core and an inner cladding generally surrounding the core. The photonic bandgap fiber is in optical communication with the optical coupler. Light signals counterpropagate through the photonic bandgap fiber and return to the optical coupler. The photonic bandgap fiber has a phase thermal constant S less than 8 parts-per-million per degree Celsius.

This technology is available for licensing through Stanford's exclusive licensee. Please contact Dennis Fortner at: Dennis.Fortner@ngc.com for more information.

### **Applications**

 A method to reduce the thermal drift in a fiber optic gyroscope, by using an aircore fiber, andmethods to reduce the residual thermal drift by properly designing the air-core fiber."

#### **Patents**

Published Application: <u>20080030741</u>
Published Application: <u>20100039649</u>

Issued: <u>7,619,743 (USA)</u>
Issued: <u>7,911,620 (USA)</u>

#### **Innovators**

Michel Digonnet

- Vinayak Dangui
- Gordon Kino
- Hyang Kyun Kim

# **Licensing Contact**

## Luis Mejia

Senior Licensing Manager, Physical Sciences

<u>Email</u>