

Measuring strains and other perturbations using slow light in an FBG configured in transmission or reflection

An optical device, a method of configuring an optical device, and a method of using a fiber Bragg grating is provided. The optical device includes a fiber Bragg grating, a narrowband optical source, and at least one optical detector. The fiber Bragg grating has a power transmission spectrum as a function of wavelength with one or more resonance peaks, each comprising a local maximum and two non-zero-slope regions with the local maximum therebetween. The light generated by the narrowband optical source has a wavelength at a non-zero-slope region of a resonance peak that is selected such that one or more of the following quantities, evaluated at the resonance peak, is at a maximum value: (a) the product of the group delay spectrum and the power transmission spectrum and (b) the product of the group delay spectrum and one minus the power reflection spectrum.

This technology is available for licensing through Stanford's exclusive licensee. Please contact Dennis Fortner at: Dennis.Fortner@ngc.com for licensing information.

Applications

- The invention is used as strain/temperature sensor with ultra high sensitivity.

Advantages

- The benefit of using this FBG sensing scheme is to improve the sensitivity to a perturbation and simplify the engineering required to stabilize the sensor.

Patents

- Published Application: [WO2013109987](#)
- Published Application: [20130193961](#)
- Published Application: [20150211918](#)
- Issued: [9,025,157 \(USA\)](#)
- Issued: [9,347,826 \(USA\)](#)

Innovators

- He Wen
- Michel Digonnet
- Shanhui Fan

Licensing Contact

Evan Elder

Associate Director, Licensing and Strategic Alliances, Physica

[Email](#)