

An ultra-high areal loading MnO₂ electrode

Stanford researchers within the Cui Lab have discovered a promising practical application for grid-scale energy storage by solving poor electronic conductivity in Mn based aqueous batteries, resulting in cycling with an **ultra-high areal loading of 20 mAh cm⁻² for over 200 cycles with only 13% capacity loss.**

Poor electronic conductivity of electro-deposited MnO₂ is a key critical problem that limits the maximum specific areal loading, producing only a thin layer of MnO₂ with low areal loading (around 0.005~0.05 mAh cm⁻²) during the charge/discharge cycle. Stanford researchers discovered, by tuning the temperature, the deposited phase of MnO₂ can be manipulated from α -MnO₂ with low conductivity to γ -MnO₂ with 2 orders of magnitude increase in conductivity.

Stage of Development

- Proof-of-Concept

Applications

- Potential use for manganese-hydrogen and manganese-zinc aqueous batteries in **grid-scale energy storage**

Advantages

- **More efficient:**
 - Can be cycled with 20 mAh cm⁻² for over 200 cycles with only 13% capacity loss
 - Increase in electronic conductivity of electro-deposited MnO₂ **by 2-3 orders of magnitudes** compared to conventional Mn²⁺/MnO₂ electrode (from 0.005~0.05 mAh cm⁻² to 33 mAh cm⁻²)

- Increase in electronic conductivity **by 100~1000 folds** compared to other doping methods to modify MnO₂ materials, and temperature dependent tuning technique maintains its polymorph during cycling
- **Scalable**
- **Lower overall cost** for manganese-based batteries
- **Safer** than fire-risk lithium-ion batteries

Publications

- Xiao, X., Zhang, Z., Wu, Y., Xu, J., Gao, X., Xu, R., ... & Cui, Y. (2023). [Ultrahigh-loading Manganese-based Electrode for Aqueous Battery via Polymorph Tuning](#). *Advanced Materials*, 2211555.

Innovators

- Xin Xiao
- Yi Cui
- Zewen Zhang

Licensing Contact

Jon Gortat

Licensing & Strategic Alliances Director for Physical Science

[Email](#)