


Architecture for scalable, large bandwidth, low loss millimeter wave (MMW) antenna arrays

Researchers in the Arbabian Lab at Stanford have developed a scalable antenna architecture that uses low-loss dielectric waveguides to achieve passive, phase-coherent signal distribution across large (>30 wavelengths) millimeter-wave (mm-wave) arrays for communications and radar applications.

Conventional interconnects for mm-wave arrays suffer from high transmission loss and limited bandwidth. This patented invention solves those problems by distributing signals directly at mm-wave frequencies through dielectric waveguides for very efficient signal distribution over large baselines, with no local frequency conversion hardware required. This technology can greatly increase capacity of short range (chip-to-chip or board-to-board) to medium range (rack-to-rack) wireless communications links and improve resolution in imaging and radar systems.



mm-wave arrays with two or more subarray modules (101), a central processing unit (102) and mm-wave/sub-mm-wave low-loss interconnects (103)

Figure 1 - Diagram of passive, phase-coherent mm-wave signal distribution via dielectric waveguides

(Image courtesy the Arbabian Lab)

Stage of Development: Prototype

Loss and bandwidth performance demonstrated experimentally.

Applications

- **RF antenna arrays**
- Radar (phased array antennas) and high-resolution imaging systems
- 5G, backhaul, and last-mile wireless communications networks (beam-forming antennas)
- Automotive radar and sensing, drone and mobile platform communications
- High-speed data center interconnects

Advantages

- Large aperture: >30 wavelengths
- Very low signal loss and wide bandwidth compared to conventional metallic mm-wave waveguides
- Passive phase coherence across large array baselines, no active stabilization required
- Eliminates local frequency up/down conversion, reducing subarray hardware complexity
- Strong immunity to electrical interference
- Scalable across the 20 to 500 GHz frequency range
- Improves imaging resolution and wireless link capacity compared to conventional architectures
- CMOS-compatible fabrication

Publications

- Dolatsha, N., Arbabian, M. A., & Mamandipoor, B. (2021). *U.S. Patent No. [11,101,828](#)*. Washington, DC: U.S. Patent and Trademark Office.

Patents

- Published Application: [WO2018195453](#)
- Published Application: [20210135691](#)
- Issued: [11,101,828 \(USA\)](#)

Innovators

- Nemat Dolatsha
- Mohammad Arbabian
- Babak Mamandipoor

Licensing Contact

Evan Elder

Associate Director, Licensing and Strategic Alliances, Physica

[Email](#)